



TorTech Pty. Ltd.

Total Transformer Solutions ABN 36 003 233 350

PO Box 194
North Strathfield NSW 2137
4/31 Wentworth St
Greenacre NSW 2190

Tel: (02) 9642 6003
Fax: (02) 9642 6127
E-mail: tortech@ozemail.com.au
Website: www.tortech.com.au

GENERAL PURPOSE ENCLOSED LOW VOLTAGE STEPDOWN TRANSFORMERS



Part Number	Part Number	Rating VA	L (mm)	W (mm)	H (mm)	Weight kg
SD120-12+12	SD120-32	120	190	145	95	2.5
SD225-12+12	SD225-32	225	240	155	125	3.5
SD300-12+12	SD300-32	300	240	155	125	4.5
SD400-12+12	SD400-32	400	240	155	125	5
SD500-12+12	SD500-32	500	280	155	145	5.5
SD625-12+12	SD625-32	625	280	155	145	6.5

- Input voltage 240V at 50Hz
- Output voltage 2*12V or 32V
- Input and output Terminals (hard wired)
- All units are double wound-(Fully Insulated)
- All enclosures are metal, with Powder Coat finish
- All enclosures are earthed to chassis
- Designed to Australian Standard AS 61558.1:2000
- 100% electrical & flash tested
- All units are fused protected on the input side.

➤ ***Details are subject to change without written notification***



TorTech Pty. Ltd.

Total Transformer Solutions ABN 36 003 233 350

PO Box 194
North Strathfield NSW 2137
4/31 Wentworth St
Greenacre NSW 2190

Tel: (02) 9642 6003
Fax: (02) 9642 6127
E-mail: tortech@ozemail.com.au
Website: www.tortech.com.au

- ***Tortech's design format facilitates a wide range of output voltages, configurations and termination possibilities. Please discuss your specific requirements with our sales staff.***